

Equipment

Equipment list

Manually operated grease pump	Classification	Type	Discharging amount cm ³ /stroke		Tank capacity (ℓ)	Maximum working pressure (MPa)	Remarks		Page	
	KM	KM-42AK	3.5		2	21	For grease		12	
		KM-52AK			4		For grease			
		KM-32AKP			1.6		For grease			
		KM-52AKP			3		For grease			
	KM-3BKP	7		1.6	10	For oil				
KM-5BKP	3			For oil						
Motor driven grease pump	Classification	Type	Discharging amount (cm ³ /min)		Tank capacity (ℓ)	Maximum working pressure (MPa)	Electric motor output (MPa)	Remarks	Page	
	AKA	AKA-104AK	30	1500min ⁻¹ 50Hz	1800min ⁻¹ 60Hz	4	21	0.1	For grease	14
		AKA-108AK				8				
		AKA-115AK				15				
		AKA-125AK				25				
		AKA-104AKP				4				
		AKA-108AKP				8				
	AKA-104BKP	30	90	36	4	10	0.1	For oil	16	
	AKA-108BKP				8					
	LBP	LBP08	75	90	Drum can of 200 ℓ	21	0.2	For grease		
LBP40		316	380	0.4				For grease (for multi-zone system)		
Distributing valve	Classification	Type	Discharging amount cm ³ /stroke		Number of ports	Maximum working pressure (MPa)	Remarks		Page	
	MJN	MJN-3-8	0.082-0.492		2-16	14	For grease and oil, for intermittent lubrication		18	
	M · MO	M-3-8	0.164-10148		2-16	21	For grease and oil, for intermittent lubrication			
		MO-3-8	0.164-10148			10	For oil, for circulating lubrication			
	MX · MXO	MX-3-8	0.410-4.920		2-16	21	For grease and oil, for intermittent lubrication			
		MXO-3-8	0.410-4.920			10	For oil, for circulating lubrication			
MG	MG-3-8	2.460-19.68		2-16	10	For oil, for circulating lubrication				
Grease filling pump	Classification	Type	Designation	Discharging amount (cm ³ /min)		Electric motor (kW) 4P	Discharging pressure (MPa)	Remarks	Page	
	Manual	PF-1-20	Filler back	40cm ³ /Stroke						—
		PF-3-20	Filler back	40cm ³ /Stroke		—	2			
	Electric	EFP-10	Filler back	175	210	0.04	1	For drum can of 200 ℓ		
BA-2 * HN-10		Barrel pump	520	630	0.4	6				
Spray nozzle	Classification	Type	Maximum working pressure (MPa)	Minimum operating pressure	Air consumption (N ℓ /min)	Remarks		Page		
	BSV	BSV-1	5.0 (Lubricant)	1.5	380	Automatic air open/close system interlocked with lubricant		—		
		BSV-3	5.0 (Lubricant)	—	120	—				